



ESKAY
holographics
L T D

UNITS 9 & 10, OPTREX BUSINESS PARK,
ROTHERWICK,
NR. HOOK
HAMPSHIRE
RG27 9AY
UNITED KINGDOM

TEL: +44 (0) 1256 760077
FAX: +44 (0) 1256 763111
EMail: sales@eskayholographics.co.uk

SPECIFICATIONS FOR THE STANDARD SPECIFICATION.

S610SKEF ELECTROFORMING MODULE AND RECTIFIER

610 mm square pp tank
2 kW ptfе immersion heater
Vertical circulation pump and filter
Circulation pipe-work
ss steel anode and cathode rods
Anode basket
25 amp single phase rectifier

Mounted within a 304 Stainless steel frame is the pp tank, which will have internal fittings as below;

PTFE 2 kW heater to side of tank at rear
Pump and filter unit at rear of tank
PP pipe-work for circulation and agitation with eductors for increased solution movement
Cathode and anode bars in stainless steel
Tank lid to reduce fumes
Wiring for heater, pump and dc power from control cabinet
25 amp rectifier within PC control cabinet as above

Wiring is included which will allow maximum 1.5 metres between the module and the control cabinet.

TO BE CONTROLLED BY THE PC CONTROL SYSTEM: